



let's make it **easy**

Commercial **Cable Router**

Model: **DDC2700**

Overview

The Ubee DDC2700 Commercial Cable Router is an advanced device designed to support the needs of commercial users. The combination of a DOCSIS 2.0 cable modem, router, firewall, and 4-port switch allows for a complete SMB solution. This highly capable commercial cable router provides state-of-the-art filtering and controls allowing administrators to limit URL access and monitor Internet activities. And it's equipped with a double firewall (SPI + NAT) protection to secure computers and networks against hackers.



Key Features & Benefits

- **Robust Security**

Stateful Packet Inspection Firewall that supports TCP/UDP inspection, DoS (Denial of Services) detection and prevention, real time alert, reports and logs.

- **Advanced Routing Features**

With the ability to enable VPN, ACLs, RIPv2, multiple subnets, 1:1 NAT, and many more MSOs can successfully place the Wireless Cable Router into any commercial and residential environment.

- **TACACS+/RADIUS**

TACACS+/RADIUS Telenet Remote Administration authentication provides added security as to who can manage the gateway.

- **Increased Memory**

With 32MB DDR Ram on board, Ubee has the capability to add features and functionality to fit the MSOs needs.

- **Multiple Public IP Addresses**

With the ability to handle multiple publicly routed IP addresses, SMB owners can use multiple subnets to partition their internal networks the way they desire.

Commercial Cable Router

Model: DDC2700



Product Specifications

Hardware

- Cable Interface: F-Connector, female
- CPE Interface: USB 1.1 and 10/100 Based-T RJ-45 Port
- Dimensions: 4.8" (L) x 5" (W) x 1.25" (H)
- Power Consumption: Maximum 8W
- Power Supply: 12V @ 1.0A
- Input Power: 100 ~ 240VAC, 50 ~ 60Hz
- Operating Temp.: 0°C to 40°C (32°F to 104°F)
- Humidity: 5 ~ 95% (non-condensing)

Downstream

- Frequency Range: 88 MHz ~ 860 MHz
- Modulation: 64/256 QAM
- Maximum Data Rate*:
 - 30Mbits/sec (64QAM)
 - 42.8Mbits/sec (256QAM)
- Symbol Rate: 5.057/5.361/Msymbols/sec
- RF Input/Output Power:
 - 17 to +15dBmV (64 QAM)
 - 15 to +17dBmV (256 QAM)
- Input Impedance: 75 Ω
- Channel Bandwidth: 6 or 8 MHz

Upstream

- Frequency Range: 5 MHz ~ 42 MHz
- Modulation:
 - A-TDMA: QPSK 8, 16, 32, 64QAM
 - S-CMDA: QPSK 8, 16, 32, 64, 128QAM
- Maximum Data Rate:
 - 0.32 ~ 10.24Mbits (QPSK)
 - 0.64 ~ 20.48Mbits (16QAM)
 - 0.96 ~ 30.72Mbits (64QAM)

RF Output Power:

- A-TDMA:
 - +8dBmV ~ +58dBmV(QPSK)
 - +8dBmV ~ +55dBmV(QAM)
 - +8dBmV ~ +54dBmV (32/64)

*Actual speeds will vary based on factors including network configuration and speed

www.ubeeinteractive.com

1.888.390.8233



The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. Ubee disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without the express written permission of Ubee is strictly forbidden.